



Type TF 11

modular @temp

Temperature sensor according to DIN with neck pipe

Basic features

- ▶ standard process adaption with 1/2" welding sleeve
- ▶ protective fitting with neck pipe according to DIN 43 763 made of high-grade steel, material No.1.4571
- ▶ changeable measuring element (without opening the process)
- ▶ changeable connecting head
- ▶ optional: with free programmable integrated measuring transducer 4...20 mA
- ▶ optional: calibration certificate according to DIN ISO 9000 ff (see data sheet calibr.-service)

Technical features

- ▶ 1 or 2xPt100 class A
- ▶ Neck pipe length = 120 mm (other length on request)
- ▶ standard-functional range -50°C to 400°C (other ranges on request)
- ▶ Alu / High-grade steel connecting head with bolting or M12-plug
- ▶ diameter of protective tube: 9 x 1 mm
- ▶ protection class (execution-dependently)
- ▶ operating pressure 30 bar max.

Favoured fields of application are e.g.:


- ▶ temperature measuring in isolated containers and pipings
- ▶ standard process application in rough environment
- ▶ standard temperature measuring; measuring in positive pressure- and under inflation containers and pipings




example: TF11-5-A-1A3


Pin assignment M12-plug

With measuring transducer MUK



Without measuring transducer MUK





Type TF 11

modular @temp

Order Code

TF 11 - [] - [] - [] [] [] - []

Connecting head

SB (IP54) with screw -cap	1
SBKL (IP65) with hinged lid	2
SBKS (IP54 with hinged lid quick release fastener	3
SBAKLH (IP65 with high hinged lid (for meas. transducer)	4
SBVA (high-grade-steel 1.4571, IP65), small vers., screw connection	5
SBVAST (high-grade-steel 1.4571, IP65, like 5 w.o.screw conn., M12-plug)	6
SBVAG (high-grade-steel 1.4571, IP65), large version,screw connection)	7
SBVASTG (high-grade-steel, 1.4571, IP65, like 7 w.o. scr.conn., M12-plug	8
SBVAH (high-grade-steel 1.4571, IP65) large version.,high lids for 2 MT	9
SBVASTH (high-grade-steel 1.4571, IP65, like 9 w.o scr.conn, M12-plug)	10

Fitting length (ML = mouting length), (MEL = measuring element length)

50 mm ML (MEL = 205 mm)	A
100 mm ML (MEL = 255 mm)	B
160 mm ML (MEL = 315 mm)	C
200 mm ML (MEL = 355 mm)	D
250 mm ML (MEL = 405 mm)	E
400 mm ML (MEL = 555 mm)	F
K - Customers preference (Please specify the length)	K

Type of sensor and tolerance

1xPt100, class A, 2-wire	1	A	2
2xPt100, class A, 2-wire	2	A	2
1xPt100, class A, 3-wire	1	A	3
2xPt100, class A 3-wire	2	A	3
1xPt100, class A 3-wire	1	A	4
other type or customized classification on request			K

Output signal

Additional name for integrated sensor-head transducer	MUK
Specification of the temperature range	

The red marked items are preferred types!