

Type SSG-1

Universal setpoint transmitter + simulator

Advanced Features

- ▶ Digital menu-driven adjustment
- ▶ Switchable menu-languages D, GB, F, E, I
- ▶ Background-lit graphic LC-display
160 x 160 Pixel
- ▶ Stair, ramp, cycle, HOLD and scaling functions
- ▶ Stair, ramp, cycle, HOLD and scaling functions
- ▶ Editable display unit, real-time clock, fast calling (%FS)
- ▶ Average-, MIN/MAX-, OFFSET-functions valve test
- ▶ Power supply by 4 x 1,5V batteries
- ▶ Incl. wrist-strap, battery-set
- ▶ Protection class: IP 54



Technical features

- ▶ Signals
(mA) current 0(4)...20 mA, 25 mA
current adjustable in 0,001 mA-steps
(V) Spannung 0...10V, 25V, 50V
Voltage adjustable in 0,001 V-steps
- ▶ Transmitter-supply 24 VDC / 22 mA
- ▶ Accuracy +/- 0,015% of rdg. + K
- ▶ Resolution 0,001 mA resp. 0,001 V
- ▶ incl. 2 x test leads, 2 x croco clips

Accessories



Carry Bag (without unit)

Favoured fields of application are e.g.:

- ▶ Simulating and measuring Programmable checkpoints

Order code SSG-1

SSG-1

Options

- DKD-Certificate
- Calibrating with feedback verification
- internal Accumulator set Ni-MH incl. charging device
- Carry Bag