

Type TF 11

modular @ temp

Temperature sensor according to DIN with neck pipe

Basic features

- ▶ standard process adaption with 1/2" welding sleeve
- ▶ protective fitting with neck pipe according to DIN 43 763 made of high-grade steel, material No.1.4571
- ▶ changeable measuring element (without opening the process)
- ▶ changeable connecting head
- ▶ optional: with free programmable integrated measuring transducer 4...20 mA
- ▶ optional: calibration certificate according to DIN ISO 9000 ff (see data sheet calibr.-service)



Technical features


- ▶ 1 or 2xPt100 class A
- ▶ Neck pipe length = 120 mm (other length on request)
- ▶ standard-functional range -50°C to 400°C (other ranges on request)
- ▶ Alu / High-grade steel connecting head with bolting or M12-plug
- ▶ diameter of protective tube: 9 x 1 mm
- ▶ protection class (execution-dependently)
- ▶ operating pressure 30 bar max.

Favoured fields of application are e.g.:


- ▶ temperature measuring in isolated containers and pipings
- ▶ standard process application in rough environment
- ▶ standard temperature measuring; measuring in positive pressure- and under inflation containers and pipings


Pin assignment M12-plug

With measuring transducer MUK



Without measuring transducer MUK



**Type TF 11****modular @temp**

Order Code

temperature sensor Type TF 11

TF 11 - <input type="text"/> - <input type="text"/> - <input type="text"/> <input type="text"/> <input type="text"/> - <input type="text"/>									
Connecting head									
SB (IP54) with screw -cap	1								
SBKL (IP65) with hinged lid	2								
SBKS (IP54 with hinged lid quick release fastener	3								
SBAKLH (IP65 with high hinged lid (for meas. transducer)	4								
SBVA (high-grade-steel 1.4571, IP65), small vers., screw connection	5								
SBVAST (high-grade-steel 1.4571, IP65, like 5 w.o.screw conn., M12-plug)	6								
SBVAG (high-grade-steel 1.4571, IP65), large version,screw connection)	7								
SBVASTG (high-grade-steel, 1.4571, IP65, like 7 w.o. scr.conn., M12-plug	8								
SBVAG (high-grade-steel 1.4571, IP65) large vers. with assembly kit for 2 MT	9								
SBVASTH (high-grade-steel 1.4571, IP65, like 9 w.o scr.conn, M12-plug)	10								
Fitting length (ML = mouting length), (MEL = measuring element length)									
50 mm ML (MEL = 205 mm)		A							
100 mm ML (MEL = 255 mm)		B							
160 mm ML (MEL = 315 mm)		C							
200 mm ML (MEL = 355 mm)		D							
250 mm ML (MEL = 405 mm)		E							
400 mm ML (MEL = 555 mm)		F							
Customized, Length <400mm, price of the next higher standard length		K							
Customized, Length > 400 mm, Base price of 400 mm, + 10,00 euro per started 100 mm									
Type of sensor and tolerance									
1xPt100, class A 4-wire			1	A	4				
2xPt100, class A 3-wire			2	A	3				
other type or customized classification on request					K				on request
Output signal									
Additional name for integrated sensor-head transducer								MUK	
Specification of the temperature range									

The red marked items are preferred types!